

Claim Proposed by Examiner
07 June 2007

1 A support for a shower head, comprising:

2 a mounting fixture for mounting the support such that the support is adjustable,

3
4 a pivotal an arm jutting out of the mounting fixture, said arm having a first
5 end connected to the mounting fixture and a second opposite end, wherein
6 said arm comprises a length of hollow profiled stock, at least from the
7 mounting fixture to the additional shower fixture

8
9 a receptacle adapted to a receive the shower head when not in operation,
10 said receptacle being arranged at said second opposite ~~for a shower head~~
11 ~~arranged in the vicinity of a far end of the arm away from the mounting fixture,~~
12 ~~which receptacle is configured such that the shower head is detachable from said~~
13 ~~receptacle, wherein the shower head and the receptacle are configured to~~
14 allow the shower head to be removed from the receptacle during operation,
15
16 and

17
18 at least one additional shower fixture attached to the arm,

19
20 wherein the shower head is supplied with water by a hose and wherein the
21 additional shower fixture is arranged to be supplied with water by said hollow
22 arm independently of the shower head.

Claim Proposed by Applicant
08 June 2007

1 1(for discussion). A support for a shower head, comprising:

2 a mounting fixture for mounting the support ~~such that the support is~~
3 ~~adjustable,~~ and an arm jutting out of the mounting fixture, wherein the support
4 is adjustable for pivoting the arm relative to the mounting fixture, said arm
5 having a first end connected to the mounting fixture and an opposite end,
6 a receptacle adapted to receive the shower head, the receptacle being
7 arranged adjacent to said opposite ~~for a shower head arranged in the vicinity~~
8 ~~of a far end of the arm away from the mounting fixture, which receptacle is~~
9 ~~configured such that the shower head is detachable from said receptacle,~~
10 wherein the shower head and the receptacle are configured to allow the
11 shower head to be removed from the receptacle for hand operation of the
12 shower head, and

13 at least one additional shower fixture attached to the arm, wherein the
14 shower head is supplied with water by a hose and wherein the additional shower
15 fixture is arranged to be supplied with water independently of the shower head,
16 by a conduit extending along the arm from the mounting fixture at least to
17 the additional shower fixture.